


Art. no.	Article						
82.8420	Drop-down support rail with spring load ▪ for the washstand and WC area ▪ optimal grip and support: double-elliptical/triangular hand grip shape with direction-neutral cross-section (42 x 45 mm) ▪ with grip-side holder element designed as a cover plate (214 x 105 mm) for concealed fixing ▪ ease of action adjustable ▪ special lengths up to max. 900 mm also available on request Material: aluminium, powder-coated Load-bearing capacity: tested up to 200 kg supports up to 60 kg of lateral load solid/combined (see p. 27) <table><tr><td>.00070</td><td>L = 700 mm</td></tr><tr><td>.00085</td><td>L = 850 mm</td></tr><tr><td>.00090</td><td>L = 900 mm</td></tr></table>	.00070	L = 700 mm	.00085	L = 850 mm	.00090	L = 900 mm
.00070	L = 700 mm						
.00085	L = 850 mm						
.00090	L = 900 mm						



82.8420	Drop-down support rail with spring load and LED function button ▪ for the WC area ▪ optimal grip and support: double-elliptical/triangular hand grip shape with direction-neutral cross-section (42 x 45 mm) ▪ with grip-side holder element designed as a cover plate (214 x 105 mm) for concealed fixing ▪ ease of action adjustable ▪ LED function button (red/white) features both a closer and opener function ▪ concealed cable routing: carried out within the grip through the support plate directly into the wall installation, no visible cable ▪ compatible with all standard concealed cisterns with electric control ▪ special lengths up to max. 900 mm also available on request Material: aluminium, powder-coated function button: plastic Load-bearing capacity: tested up to 200 kg supports up to 60 kg of lateral load Technical data: degree of protection: IP67 contact ratings: 32 V AC, 400 mA / 50 V DC, 100 mA contact resistance: max. 50 mΩ bounce time: 1 ms insulation resistance: 1 GΩ dielectric strength: 1.000 V AC actuation force: 3 N solid/combined (see p. 27) <table><tr><td>.00570</td><td>L = 700 mm</td></tr><tr><td>.00585</td><td>L = 850 mm</td></tr><tr><td>.00590</td><td>L = 900 mm</td></tr></table>	.00570	L = 700 mm	.00585	L = 850 mm	.00590	L = 900 mm
.00570	L = 700 mm						
.00585	L = 850 mm						
.00590	L = 900 mm						

